




Technical specifications

Power supply: 24V DC
 Power consumption: 30W (max)
 Fusing: built in trip switch with push button reset
 CE approved

Performance

21 days preservation
 Resealing time: 1 – 5 seconds
 Each system is pre-set to operate at altitudes between 0 – 500m; for locations above this level please refer to the manufacturer or your local dealer



What's included with each system

- 20x still wine eStoppers (excl. Champagne only models)
- 6x sparkling wine stoppers (excl. still wine only models)
- A pre-set CO2 regulator (excl. still wine only models)
- 5m length of CO2 hose (excl. still wine only models)
- Power supply configured to your region, complete with 1.5m cable
- Mounting kit
- 12 month warranty

Sourcing CO2: Outside the UK the only item that needs sourcing locally is a food-grade CO2 supply to support sparkling wine preservation. We will be happy to recommend preferred suppliers in your market, please contact us directly.

Product	Model No.	Wine Preservation		Height		Width		Depth	
		Still	Sparkling	mm	inch	mm	inch	mm	inch
Classic	BC02	Yes	Yes	550	21.6	135	5.3	130	5.1
Classic - Still wine only	BC02S	Yes	No	550	21.6	135	5.3	130	5.1
Classic - Sparkling wine only	BC02C	No	Yes	550	21.6	135	5.3	130	5.1

Product	Model No.	Wine Preservation		Height		Width		Depth	
		Still	Sparkling	mm	inch	mm	inch	mm	inch
Classic Steel Edition	BC02SE	Yes	Yes	550	21.6	135	5.3	130	5.1
Classic Steel Edition - Still wine only	BC02SES	Yes	No	550	21.6	135	5.3	130	5.1
Classic Steel Edition - Sparkling wine only	BC02SEC	No	Yes	550	21.6	135	5.3	130	5.1