



Technical specifications

Power supply: 24V DC
 Power consumption: 30W (max)
 Fusing: built in trip switch with push button reset
 CE approved

Performance

21 days preservation
 Resealing time: 1 – 5 seconds
 Each system is pre-set to operate at altitudes between 0 – 500m; for locations above this level please refer to the manufacturer or your local dealer



What's included with each system

- 20x still wine eStoppers (excl. Champagne only models)
- 6x sparkling wine stoppers (excl. still wine only models)
- A pre-set CO2 regulator (excl. still wine only models)
- 5m length of CO2 hose (excl. still wine only models)
- Power supply configured to your region, complete with 1.5m cable
- Mounting kit
- 12 month warranty

Sourcing CO2: Outside the UK the only item that needs sourcing locally is a food-grade CO2 supply to support sparkling wine preservation. We will be happy to recommend preferred suppliers in your market, please contact us directly.

Product	Model No.	Wine Preservation		Height		Width		Depth	
		Still	Sparkling	mm	inch	mm	inch	mm	inch
Tower	BC06	Yes	Yes	510	20	120	4.7	135	5.3
Tower - Still wine only	BC05S	Yes	No	510	20	120	4.7	135	5.3
Tower - Sparkling wine only	BC05C	No	Yes	510	20	120	4.7	135	5.3

Product	Model No.	Wine Preservation		System						Base			
		Still	Sparkling	Height (mm)	Height (Inch)	Width (mm)	Width (Inch)	Depth (mm)	Depth (Inch)	Width (mm)	Width (Inch)	Depth (mm)	Depth (Inch)
Tower Portable Edition	BC06P	Yes	Yes	520	20.5	120	4.7	295	11.6	230	9	380	15
Tower Portable Edition - Still wine only	BC05PS	Yes	No	520	20.5	120	4.7	135	5.3	230	9	380	15
Tower Portable Edition - Sparkling wine only	BC05PC	No	Yes	520	20.5	120	4.7	295	11.6	230	9	380	15